







REF.	FA 50 211 75
CE	EN 362:2004 Class A
	20 kN / 75 mm
MAT.	
	DOUBLE ACTION
KEYLOCK	---
+	---
	0.30 KG

	MAT.	
Résistance à la rupture / Ouverture	Matière	Type d'ouverture
Breaking strength / Gate opening	Material	Opening system
Resistencia a la ruptura / Apertura	Material	Tipo de apertura
Resistenza alla rottura / Apertura	Materia	Sistema di apertura
Bruchfestigkeit / Öffnung	Material	Öffnungssystem

HS CODE
73262000
CARTON SIZE / PCS.
60x40x24/50
AET (EU) N°2777/10356-03/E01-01
Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
MODULE D FI14/14003.01
SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland
AET (UKCA) N°AB0321/16038-01/E01-01
Satra Technology Centre, N°0321 Wyndham Way, Telford Way, Kettering Northamptonshire, NN16 8SD, United Kingdom
MODULE D 11 IN14/14003
SGS United Kingdom Ltd., N°0120 Unit 202B, Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom