


**PRODUCT SHEET ULTRA HIGH PRESSURE PROTECTIVE BOOT  
Art. N° 1325**

Name 1325  
 Category S5  
 Size 41-48  
 Colour Black and  
 as picture  
 Weight(43)gr. 3.640  
 1 pair

Protective boot for high-pressure water jets (1.200 bars), produced according to Norm ISO/EN 20345 - S5.  
 The additional protection consist on a thick layer of patented material, which protect from high pressure jetting up till 1.200 bars. Article 1325 is produced with first quality raw materials and high quality pvc blend; hence, technical and endurance distinctive features keep this boot at a high quality position which means long life.  
 This boot is produced in the full respect of the environment, thanks to the ecological raw materials used with a low content of chlorine, and completely free of lead, cadmium and barium.



**SAFETY TECHNICAL SPECIFICATIONS**

 Brevetto/Patent n. 256844	
Lance reaction force	253 N
Nozzle size, circular orifice	1,2 mm
Nozzle distance from the boot	75 mm
Feed speed	0,2 m/s
Flow rate	31,2 l/min
The above mentioned parameters equal a pressure of (see table) of the water at the nozzle	1200 bar
Passage above the front of the foot behind the protection capsule in correspondence with the instep	

**DISTINCTIVE FEATUTURES**

- ISO/EN 20345 - SRC - S5 Certificate
- Steel mid-sole and steel toe-cap
- Ultra High Pressure protection
- High quality pvc blend
- Shock-absorbing sole
- Antistatic properties
- Self-cleaning outsole
- Malleolus protection
- Foot instep extra-protection
- Front strapping protection
- Integrated pull-off spur
- Inner nails to hold overalls and trousers
- No-mould washable sock
- Anatomical foodpad