











 II2 G Exh IIC T6 Gb



<b>HS CODE</b>
63079098
<b>CARTON SIZE / PCS.</b>
60 x 40 x 24 cm / 12
<b>AET N°2777/10962-01/E01-01</b>
<b>Satra Technology Europe Ltd., N° 2777,</b> Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
<b>MODULE D FI14/14003.02</b>
<b>SGS Fimko Oy, N°0598</b> Takomotie 8, 00380 HELSINKI, Finland
<b>AET (UKCA) N°AB0321/16021-01/E01-01</b>
<b>Satra Technology Centre, N°0321</b> Wyndham Way, Telford Way, Kettering Northamptonshire, NN16 8SD, United Kingdom
<b>MODULE D 11 IN14/14003</b>
<b>SGS United Kingdom Ltd., N°0120</b> Unit 202B, Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom
<b>ACKNOWLEDGEMENT OF RECEIPT N°11ATEX6276X</b>
<b>Sira Certification Service</b> Unit 6 Hawarden Industrial Park, Hawarden, CH5 3US, UK

REF.	FA 30 403 15
LG.  KG	1.5 m (connectors included) ----- Max. 100 KG
CE	EN 355:2002
MAT.	 : 45 mm PES
	45 mm
	 FA 50 103 22 / FA 50 208 60
	NO
+	 II 2G Ex h IIC T6 Gb, EN 1149-1, ISO 80079-36, ISO 80079-37, PPE-R 11.063
	1.49 kg



**Largeur de l'absorbeur d'énergie**  
Width of the energy absorber  
**Ancho del absorbedor de energía**  
Larghezza del assorbitore di energia  
**Breite des Falldämpfers**

LG.



**Longueur Poids maxi utilisateur**  
**Length** Max. user weight  
**Longitud** Peso máximo del usuario  
**Lunghezza** Peso Max. dell'utente  
**Länge** Höchstgewicht des Benutzers



**Matière connecteur haut / connecteur bas**  
Material of top connector / bottom connector  
**Material conector alto / conector bajo**  
Materiale connettore alto / connettore basso  
**Material oberes / unteres Verbindungselement**

+

**Point fort**  
Key feature  
**Ventaja principal**  
Punti forti  
**Produktvorteil**



**Homologué pour le travail à proximité d'arêtes vives**  
Approved for work near sharp edges  
**Homologado para trabajo cerca de aristas vivas**  
Omologato per lavoro in prossimità di spigoli vivi  
**Zugelassen für Arbeiten in der Nähe scharfer Kanten**