



# HOPÉ



FA 30 600 10  
FA 30 600 15

①



FA 30 600 13



①

HS CODE
63079098
CARTON SIZE / PCS.
60 x 40 x 24 cm / 12
AET N°2777/10964-03/E11-01
Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
MODULE D FI14/14003.01
SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland
AET (UKCA) N°AB0321/16096-01/E01-01
Satra Technology Centre, N°0321 Wyndham Way, Telford Way, Kettering Northamptonshire, NN16 8SD, United Kingdom
MODULE D 11 IN14/14003
SGS United Kingdom Ltd., N°0120 Unit 202B, Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom

REF.	FA 30 600 13	FA 30 600 10	FA 30 600 15
<p>LG.</p> <p>KG</p>	1.3 m	1 m (connectors included)	1.5 m (connectors included)
	-----		
	Max. 100 KG		
CE	EN 355:2002		
MAT.	PA 11 mm		
	45 mm		
	---		
	NO		
+	PPE-R 11.063		
	0.77 KG	1.60 KG	1.82 KG



**Largeur de l'absorbeur d'énergie**  
Width of the energy absorber  
**Ancho del absorbedor de energía**  
Larghezza del assorbitore di energia  
**Breite des Falldämpfers**

LG.



**Longueur Poids maxi utilisateur**  
**Length Max. user weight**  
**Longitud Peso máximo del usuario**  
**Lunghezza Peso Max. dell'utente**  
**Länge Höchstgewicht des Benutzers**



**Matière connecteur haut / connecteur bas**  
Material of top connector / bottom connector  
**Material conector alto / conector bajo**  
Materiale connettore alto / connettore basso  
**Material oberes / unteres Verbindungselement**



**Ouverture**  
Gate opening  
**Apertura**  
Apertura  
**Öffnung**



**Homologué pour le travail à proximité d'arêtes vives**  
Approved for work near sharp edges  
**Homologado para trabajo cerca de aristas vivas**  
Omologato per lavoro in prossimità di spigoli vivi  
**Zugelassen für Arbeiten in der Nähe scharfer Kanten**