

**gravity-s**




**140**  
**kg**

<b>HS CODE</b>
63079098
<b>CARTON SIZE / PCS.</b>
60 x 40 x 24 / 12
<b>AET N° 2777/10958-01/E08-01</b>
<b>Satra Technology Europe Ltd., N° 2777,</b> Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
<b>MODULE D FI14/14003.01</b>
<b>SGS Fimko Oy, N°0598</b> Takomotie 8, 00380 HELSINKI, Finland

REF.	FA 30 900 20
 LG. KG	1.4 m / 2.0 m (connector included)
CE	EN 355:2002
MAT.	45 mm PES
	INTERNAL ABSORBER
	 FA 50 105 22B / FA 50 218 60
	YES
+	PPE-R 11.063
	X1 1.01 KG



**Largeur de l'absorbeur d'énergie**  
 Width of the energy absorber  
**Ancho del absorbedor de energía**  
 Larghezza del assorbitoro di energia  
**Breite des Falldämpfers**

LG.



**Longueur Poids maxi utilisateur**  
 Length Max. user weight  
**Longitud** Peso máximo del usuario  
**Lunghezza** Peso Max. dell'utente  
**Länge** Höchstgewicht des Benutzers



**Matière connecteur haut / connecteur bas**  
 Material of top connector / bottom connector  
**Material conector alto / conector bajo**  
 Materiale connettore alto / connettore basso  
**Material oberes / unteres Verbindungselement**



**Ouverture**  
 Gate opening  
**Apertura**  
 Apertura  
**Öffnung**



**Homologué pour le travail à proximité d'arêtes vives**  
 Approved for work near sharp edges  
**Homologado para trabajo cerca de aristas vivas**  
 Omologato per lavoro in prossimità di spigoli vivi  
**Zugelassen für Arbeiten in der Nähe scharfer Kanten**