

TRÉPANS CO8%



USINE

Référence
605 CO

| | |
|-------------|---------------|
| Nuance | Co8% Bi-métal |
| Utilisation | F A Ad lx Al |
| | ● ● ● ● ● |

| Diamètres mm |
|--------------|
| 14 |
| 16 (PG 9) |
| 17 |
| 19 (PG 11) |
| 20 |
| 21 (PG 13,5) |
| 22 (PG 16) |
| 24 |
| 25 |
| 27 |
| 29 (PG 21) |
| 30 |
| 32 |
| 33 |
| 35 |
| 37 (PG 29) |
| 38 |
| 40 |
| 41 |
| 43 |
| 44 |
| 45 |
| 46 |
| 48 (PG 36) |
| 50 |
| 51 |
| 52 |
| 54 (PG 42) |
| 55 |

| Diamètres mm |
|--------------|
| 57 |
| 59 |
| 60 |
| 64 |
| 65 |
| 67 |
| 68 |
| 70 |
| 73 |
| 75 |
| 76 |
| 79 |
| 83 |
| 86 |
| 89 |
| 92 |
| 95 |
| 98 |
| 100 |
| 102 |
| 105 |
| 108 |
| 111 |
| 114 |
| 121 |
| 127 |
| 140 |
| 146 |
| 152 |

