



Ostrava - Radvanice

Notified Body No. 1019

VVUÚ, a.s., Pílkartská 1337/7, 716 07 Ostrava – Radvanice, Czech Republic

www.vvuu.cz; e-mail: cov@vvuu.cz

EC type-examination certificate

according to Article 4 of the Government Order No. 21/2003 Coll. and according to Article 10 of the Council Directive 89/686/EEC (PPE) as amended by the Council Directives 93/68/EEC, 93/95/EEC and the Directive 96/58/EC of the European Parliament and the Council.


No.: 1019-152/Q/2016

Manufacturer:	Honeywell Fall Protection France SAS 35-37 RUE DE LA BIDAUDERIE 18100 VIERZON FRANCE
Product:	Honeywell Miller DuraHoist 3Pod, type Anchorage device
PPE category:	III.
Applied standards:	ČSN EN 795:2013 (identical to EN 795:2012) ČSN EN 365:2005 (identical to EN 365:2004) ČSN P CEN/TS 16415:2013 (identical to CEN/TS 16415:2013)
Base for issue of certificate:	Final Report No. 1019-018064/2016 (Integral part of this certificate)
Validity of certificate till:	2021-06-30

VVUÚ, a.s. hereby certifies that the sample of the product mentioned above meets all the relevant basic health and safety requirements of Annex No. 2 of the Government Order No. 21/2003 Coll., and of Annex II of the Council Directive 89/686/EEC as amended by the Council Directives 93/68/EEC, 93/95/EEC and the Directive 96/58/EC of the European Parliament and the Council.

2016-06-20
Date of issue




Ing. Tomáš Dorazil
Deputy Director NB 1019

Duplication of only parts of this document is subject to the approval of VVUÚ, a.s., NB 1019, Ostrava – Radvanice, Czech Republic

Description of product

Anchor device:	Anchor devices with three legs and an anchor points not on a leg
Type of anchor device:	Type B
Attachment points:	Four / one in the centre and three on the sides/
Height:	Min. 1290 mm / the biggest opening, the minimum length of legs/ Max. 2040 mm /the smallest opening, the maximum length of legs/
Circuit:	Min. 570 mm / the smallest opening, the minimum length of legs/ Max. 2400 mm / the biggest opening, the maximum length of legs/
Material:	EN AW 6063 /legs/, EN AW 5083 /head/ and DIN 1.4404 /swivel/
Number of users:	Max. 2

Picture of product

